



**MODEL:** FARM DUTY

**TYPE:** BEGCFD, BECCFD, BECSFD

Effective 02-09-23  
Supercedes All Previous

### APPLICATIONS

- Fans & Blowers
- Pumps
- Compressors
- Farm Equipment
- Machine Tools

### PRODUCT OVERVIEW

- 1/3-10 HP
- Totally Enclosed IP44 Design
- 60Hz, 115/230V OR 230V; Single Phase
- Horizontal F1 Mount
- 1800 RPM

### DESIGN FEATURES

- 1.15 S.F.
- 40°C Ambient
- Continuous Duty
- Max Elevation 3300ft
- High Torque
- Class B Insulation up to 3 HP; Class F Insulation 3-10 HP
- Class B Temperature Rise
- Capacitor Start, Induction Run .33-1.5 HP; Capacitor Start, Capacitor Run 2-10 HP

### MECHANICAL FEATURES

- Shielded Bearings
- Multemp SRL Grease
- Aluminum Rotor
- Cast-Iron Frame and End Brackets 1.5-10 HP, Rolled Steel for Others
- Rolled Steel Fan Cover and Terminal Box
- Plastic Fan
- Grounding Terminal Inside Main Terminal Box
- Paint System: Phenolic Rust Proof Base with Polyurethane Top Coat
- Rubber Flinger on DE
- Phenolic Alkyd Resin Varnish
- Manual Reset Overload

### OTHER FEATURES

- CSA approved, UL Recognized